Richard. Smiley
v
Norwich & Worcester R. R. Co

Circuit Court of
N. Hampton
October 1848.

The bill of Complaint sets forth, that the Complainant was the original and first inventor of a new and useful improvement in the manner and means of attaching the bodies of Rail Road Cars and Carriages, and connecting them with the truck, and that on the 21st day of September 1837, a Patent was granted to secure the same to him for the period of fourteen years. It also sets forth, that on or about the first day of September 1844. the said Patent was extended for seven years from the 21st day of September 1851. That the Defendants without the license of the Complainant, have been using, and at the time of the filing of the bill, were using, the improvement patented, on a large number of Cars running on the road, between Worcester in the State of Massachusetts on Albany Point, and Providence and Norwich in the State of Connecticut. The bill prays for an injunction; for an account; and for other relief. The extended Patent, has now expired. It was in force however, when the bill was filed.

Exception has been taken by the Defendants, that an injunction cannot be awarded,

that the account, and the other relief sought by ordering the account, and the hearing the other relief, and the bill cannot be granted; - that the ~~account is~~ ^ ancillary to the hearing of the injunction, and that an account cannot be ordered, unless an injunction is also ordered. The Patent act of 1836, in the 17th section thereof provides, that all actions suits controversies, and cases arising under any law of the United States, granting or confirming to inventors the exclusive right to their inventions or discoveries, shall be originally cognizable, as well in equity as at law by the Circuit Courts of the United States. And it has already been expressly decided by Judge Grier, in a case before him, on a Sealed Patent, that where, between the time of filing the bill, and the hearing, the Patent has expired, that an account could be ordered and other relief granted, though, on account of the expiration of the Patent, an injunction ~~could~~ not to restrain the future use could not issue.

The validity of the Patent is not questioned by the defendants. They admit, that the thing patented, was new and useful: that the Patent seemed to Lucky, that think it practicable to succeed to him. That part of the bill only is denied, which charges, that the defendants are using and had used ~~that~~ the device ^ the exclusive right to use which, was secured to Lucky, by the Patent.

Two questions therefore are presented for determination - I - What does the Patent purport to grant, and secure to Imlay - II - What do the defendants use - And having determined these two questions, then the fourth question will be presented Is the device used by the defendants, or any one of the devices used by them, substantially like the device or invention secured to Imlay, or any substantial portion of the same -

The invention of Imlay, was designed to afford a new and improved mode of supporting the bodies of cattle and car carriages, upon the trucks, upon which they are placed; - to supply a more safe and useful connexion, between the ~~carriage~~ truck and carriage body, than had before been known, by the support which the invention would afford to such connexion; - to move effectually, usefully and safely, unite the two ~~bodies~~, the truck and car carriage, into one, for the use for which, the car was designed, the transportation of passengers and freight; - to effectually ensure the safe keeping of the carriage on to the truck, in its proper position, by the support which it would provide, while at the same time, it would enable the car, composed of the carriage and truck, to move with facility and ease, upon the track of the road as desired - The support for the carriage body

required, was a support, while the car was in motion. And the design of the invention was, to give such support, to keep the carriage on the truck safely and securely, and in proper position, while the car was in motion. The support particularly required was, a longitudinal and lateral support. Without a longitudinal support, there would be no sufficient protection, for the carriage to remain on the truck, and in proper position, either in the forward or backward movements of the car, especially in the case of a collision, or when it should meet with any obstruction. Without a lateral support, there could be no sufficient safeguard, to protect the carriage, from being thrown off, or turned over on the side. A vertical support was also required. But such vertical support, could be of no sufficient use, in a car, moving at a rapid rate, of speed, unless there was both a longitudinal and lateral support. And the object of the Patentee, in the invention which he made, and which he describes in his specification, was to afford these support and protection in these several particulars. And by such invention, any movement was allowed in turning curves, and also a complete rotary movement if desired.

The essential means used, to accomplish

the desired result, and to afford the support required and intended, in the particulars above stated, are two cylindrical plates, one placed above and within the other, in the middle of the car, at or near each end of the car;- one strongly confined and fastened to the carriage;- the other strongly confined and fastened to the truck; and which cylinder plates, being so applied, the one entering the other, to a sufficient depth, afford the support desired and intended, without the aid of any other instrumentality.

In the specification is described, how by these means, the required support in the particulars above named is given, and the desired result is obtained, without any aid from any other instrumentality. And the description is intended to show, how by these means, the support in the particulars above named, can be effectually afforded; not only how it can be afforded in one of the particulars named, but in all of them; not only how danger is guarded against, and safety secured, from the vertical pressure, but also how, from the longitudinal and lateral pressure.

A hollow round cast iron bed plate is made, two feet in diameter, more or less, flat where the bottom, and of sufficient thickness

for strength, to support the weight, which it is intended to sustain. It has an upright rim projecting upwards, all around its periphery, two inches high more or less, and about one inch thick. The bottom of this bed plate is turned upon the inside, flat or level, and the top edge of the rim, horizontal and true, and its inner periphery vertical and smooth. A top plate of the same diameter is made, with a rim projecting downwards of nearly the same thickness as that of the bed plate rim, but not quite so deep. This is turned into the exterior rim, so as to make nearly a close fit. It has a flange projecting sufficiently, to cover the exterior rim of the bed plate, the under side of which, is turned smooth, and that to correspond to the top edge of the under rim. The interior of the top plate, is made convex, projecting downwards from the rim, towards the centre, and about one sixtenth of an inch, deeper in the finish, than the rim of the bed plate, and is all turned smooth upon the inside, and the centre is made to bear, upon the centre of the bed plate, upon a surface of four inches in diameter, more or less, and upon this centre, the whole weight of the car body and loads rest, and at the

same time allows the bed plate to vibrate or revolve under the cab plate sufficiently for all of the curves and crossings of the road, or to make an entire revolution, if desired. The bed plate is made fast upon the centre of the truck;- the cab plate is made fast to the carriage body. The centre of the cab plate, being made a grain deeper, than the height of the exterior rim, the flange of the cab plate, is left free, from the rim of the bed plate, except when the cab is out of level, at which time, the rims gripe each other, and thus prevent its being tilted out of the bed.

It will thus be seen, that by the application of these special means, as described, a mode of supporting eight Rail Road car carriages on their trucks, was accepted;- that by the connection made, by these means, a support was given to the carriage, to keep and hold it, in its proper and desired position, on the truck;- that the support and protection afforded, was a longitudinal one, when the car was moving in a forward or backward direction, or when by a collision, or any other cause force was applied to it, longitudinally;- a lateral one, when turning curves, or when the car force any cause, received a lateral or side

The devices which the defendants use and apply, to connect their car carriages with the trucks, and to give support, vertically, longitudinally and laterally to the carriages, whether on the trucks, and to keep it in its proper position, and to secure it, from being detached from the truck, and to enable the whole to work easily, safely, and securely, are the ordinary King bolt, such as is used, to connect, the carriage to the forward truck, in the common road waggon, connecting the carriage with the truck, and passing through the centre of the two Cylinder plates hereinafter mentioned;- side bearings near the sides of the carriage, resting on the truck, and which are intended, as a vertical support to the carriage, and two Cylindrical plates, male and female, one within the other, and acting in combination;- one strongly attached and fastened to the carriage truck, the other strongly attached and fastened to the carriage in the middle thereof, and at or near each end. The Cylindrical plates, used by the defendants, they call guard Collars, for the King bolt-

These devices, as they are used and applied, on the Rail Road cars, of the defendants, are intended, as it is claimed,

to be so arranged and adjusted, that the whole vertical support, is to be afforded by the side bearings:- and the whole longitudinal and lateral support, by the King bolt, or the King bolt and side bearings combined, and that the two cylinder plates are so arranged and applied, that they do not touch each other, and do not therefore afford any vertical, longitudinal or lateral support to the carriage, whether on the truck:- that they are mere guard collars, useful only, in case, the King bolt, should get out of place, or from any cause, should not perform its proper function, to hold together in their proper place the carriage and truck, and to give to the carriage the necessary longitudinal and lateral support.

In the practical operation of the devices, as applied and used by the defendants, or their case, it frequently occurs, from the wear of the side bearings, or from the manner in which the devices are adjusted, that the interior of the cap cylindrical plate, which projects downward into the cylindrical box plate, towards its bottom, is made to bear upon the bottom of the box plate, on the inside thereof, so that upon it, the weight of the car body and load rests, either wholly or in part. If for any cause, the side bearings cease to afford any

vertical support, then the whole vertical support is afforded by the Cylindrical plates. And it frequently occurs, from the wear of the King bolt, or from some defect in it, or from an adjustment of the usual device, that the inner Cylindrical plate, does actually press upon the outer one, on the inside, both longitudinally and laterally, and then by the mode in which they are applied, they do actually afford a longitudinal and lateral support. And whenever from any cause, the King bolt, and side bearings become useless, the Cylinder plates, as applied, are the only essential means, which afford the entire vertical, longitudinal and lateral support.

But I do not dispose of the case, when this limited view taken of it. For the use and application of the two Cylinder plates, one within the other, as the Defendants claim they are used and applied, on their Rail Road eight wheel Cars, would be, in violation of the rights secured to the Complainant, by his Patent. Such use and application, would give substantial support, to the Rail Road Carriage, and would be the use and application of the essential means discovered by, and patented to the Complainant, by which such support would be obtained. It is not necessary that such use and application, should be the only

essential means, by which the result is effected, to make such use of application, as infringes of the complainants Patent. If it was all Patents could be infringed by adding something to the means patented. If it, are an electrical means, though other means are used, in connexion with them, to give the required result, the Patent has been infringed; even though the object or result to be secured, by such other means in connexion, is better accomplished.

The application of the Cylinder plates, one within the other, as the defendants claim they are applied by them, is for some purpose. Before the invention of the complainant, such application, to Rail Road cars, ~~as it exists~~ has never been known. Since the general use of such application, in one form or another, to all eight wheel Rail Road cars, or most, if not all the Rail Roads in the Country, however, had such use been, or is, for a highly useful purpose. It was not in order to secure such a electrical result. The defendants say, that the Cylinder plates, as used and applied by them are merely the journal collar, for the king bolt; which king bolt, affects the longitudinal and lateral motion, to the carriage. Upon this hypothesis, they are not applied,

as an aid, to the support afforded; - as an essential means, to make that support effectual; - as an object, to make the support secure. And it has already been shown, that it is not necessary, that the way in which they are applied, should afford the sole support rendered, to make the use and application, an infringement of the patent. They are means used, the more effectually and securely, to lock and hold in proper position the carriage on the trunk. The object of support, and the meaning of the word, as it used, in the patent, are to lock and hold the carriage safely and securely, in such proper position. And the devices used by the defendants, are for that purpose. None of them are for any other purpose. The 6 cylinder plates as used by them, one within the other are for that purpose, and are effective in aid of the accomplishment of such purpose, whether called a spread collar for the king bolt, or called by any other name. Their office is, to securely and safely lock and hold, without any other instrumentality, the carriage in its proper position, on to the trunk, whenever, from any cause, the king bolt, and side bearings, are insufficient, for that purpose. When from any cause, the king bolt, and side bearings, do not perform their office, they are the only device, to lock the carriage in such proper position, and to afford it, the

necessary vertical longitudinal and lateral support.
And it is not necessary, when the Cylinder plates
have been used as offsets, as they have been
used as offsets by the defendants, that the King
bolt and side bearings should be insufficient,
before there can be an infringement of the
Patent. The Patent may be violated though
the inner Cylindrical plate may not actually
press upon the outer one.

Patents are to be construed liberally,
and are not to be subject to a strict and
rigid interpretation. The rights secured are to
be protected against any substantial violation.
Formal and subtle differences are to be disre-
garded. Where in two devices the end to be
accomplished is the same, and the substantial
means to accomplish the end, and the same,
the two devices are the identical, though one may
accomplish the end, more effectually than the
other.

With this view of the case, a decree
must be in favor of the Complainant, as
prayed for, except as to that part of the prayer,
that seeks for an injunction, to restrain a
further use. As the Patent has now expired,
an injunction against a further use, cannot
be ordered.

Respectfully
Judge.

Richard Burley

Norwich & Brandon

R R Burley

Oct 1858

Oct° 1858